

SKIM COAT TOP GREY (388)



PRODUCT DESCRIPTION

ADX™ Skim Coat Top Grey (388) is a high-quality polymer modified cementitious skim-coat with excellent spreadability, adhesion performance, open time and non-powdery surface. It is designed specifically to be used on ADX™ Skim Coat Base for smooth interior wall or ceiling to receive wall covering or painting.

FEATURE & BENEFITS

- Excellent adhesion
- Good workability
- Good crack control
- Consistent quality
- Water resistant
- High durability

TECHNICAL DATA (typical values)

Appearance	Off white powder
Binder	Cement
Filler	Graded calcium carbonate powder
Auxiliaries	Additives and specialized polymers
Water Powder Ratio	0.46 – 0.47
Wet Density	1500 – 1600 kg/m ³
Dry Density	1100 – 1200 kg/m ³
Bond Strength	≥ 0.8 N/mm ²
Coverage	25kg bag – 22.7m ² 40kg bag – 36.4m ² at 1mm thickness
Packaging	25kg; 80bags per pallet 40kg; 50bags per pallet

SURFACE PREPARATION

1. Surface to be skimmed must be structurally sound, clean and free from dust, oil and any traces of foreign materials that may affect adhesion.
2. Highly absorptive surface to be moisten with water before skimming.

MIXING

1. Mix **ADX™ Skim Coat Top Grey (388)** with approximately 11.5L (25kg) / 18.4L (40kg) of clean water.
2. Mix thoroughly with an electrical mixer for 3-5 minutes to achieve lump-free homogeneous mortar paste.

APPLICATION

1. Apply **ADX™ Skim Coat Top Grey (388)** onto the prepared surface with a steel trowel.
2. Ensure the underneath layer is dry before application of subsequent layer.

PRODUCT LIMITATIONS

Do not use **ADX™ Skim Coat Top Grey (388)** over metal/steel or painted surface.

STORAGE

ADX™ Skim Coat Top Grey (388) should be stored in dry area free from excessive moisture.

SHELF LIFE

6 months in original, unopened and undamaged sealed bags; kept off the ground in a cool, dry weatherproof environment.

HEALTH & SAFETY

ADX™ Skim Coat Top Grey (388) is non-hazardous. However, it is recommended that appropriate safety equipment be worn when handling the product, including dust mask, rubber gloves, full eye protection and safety boots where necessary. In case of contact with eyes, wash with plenty of water. If irritation persists, seek immediate medical attention. Safety Data Sheet is available upon request.

IMPORTANT NOTICE

The information provided here is based on our experience and is given to the best of our knowledge and it is non-binding. User is responsible in ensuring that the product is suitable for the purpose of the application. ADX is not liable for the use performance of the product or whatsoever arising from the use of the product unless specifically agreed in writing as we have no control on the treatment of the product and surface condition of the substrate. Edition ADX2604. This edition will become invalid when a new version is published.



022-167-3973
Environmentally Preferred Cement /
Concrete Product

Alliance Drymix (ADX) Sdn. Bhd. 200701012927 (770932-X)
No.27-2 & 29-2, Jalan Zuhrah BH U5/BH, Taman Subang Murni,
40150 Shah Alam, Selangor, Malaysia.
Phone: +603 7734 7890
support@alliancedrymix.com